

MTB	M	M-S'LriLs optionÉi L'tpÉnsion	4	Fixed suffix)					5	Fixed suffix)	
			(N A)	(M	M	M	M	S	BD	BD	OptionÉi BD ijÉrL)
			200			M		S s'LriLs optionÉi ijÉrL)			
			100			M		s'LriLs optionÉi ijÉrL)	6	/ Software/Firmware customized code and other identifiers	
			500			M		s'LriLs optionÉi ijÉrL)	ï ÿ ÿ ÿ	A ø (N A)	
3	Series model								PNP	Sourjil' tupL	
ID04	(-ijhÉnnL'i stÉnLÉrL input)										
OD04	(-ijhÉnnL'i stÉnLÉrL output)										

3. ApplijÉIJIL moLLI

NÉmL)	MoLLI)	ApplijÉIJIL ijo	► W	=	■

MoLLI ¹	²	RÉtLÉ ÉoltÉgL poolr ²	DC é mA Ch	DigitÉi input output tupL
HCMIB-ID -BD			DC é mA Ch A Ch ³	DigitÉi input DC é mA Ch
HCMIB-OD -BD	DC é é	DC é é	DC é mA Ch A Ch ³	DigitÉi output DC é mA Ch A Ch ³
HCMIB-OD -BD-PNP			DC é mA Ch A Ch ³	LoÉL tupL RLsistiÉL InLuijtiÉL LÉmp loÉLs
	LPS	SELÉ		DigitÉi output DC é mA Ch A Ch ³
				LoÉL tupL RLsistiÉL InLuijtiÉL LÉmp loÉLs

NotL All moLLIs ijÉn onlu opLrÉtL unLr thL sÉfLtu LtrÉ loo ÉoltÉgL (SELÉ) proÉiLLÉ lu É limitLÉ poolr sourijL (LPS)
ihL poolr réting inLijÉtLÉ hLrL is thL mÉtimum poolr unLr full-loÉL opLrÉtion
ConsiLr thL LÓLijt of tÉmpLrÉturtL risL ÉnL LÉrÉtL Luring using

4.2 EnÉironmÉntÉi rÉquirÉmÉnts			
	ItLm		ÁpLijixijÉtions
	Altitude		

7. InÍijËtor ÍÍsijription

[illegible]